

























O'RING FACE SEAL (ORFS)

 FF1254- (1) ORFS Plug	 FF3018- (2) ORFS Male (1) ORFS Fem. Face	 FF1311- (1) ORFS Fem. (2) TUBE Hole	 FF1204- (1) & (2) ORFS Male	 FF1234- (1) & (2) ORFS Male	 FF1220- (1) (2) & (3) ORFS Male	 FF1260LN- (1) ORFS Male (2) ORFS Male Bulkhead
 FF1261LN- (1) ORFS Male (2) ORFS Male Bulkhead	 FF1262LN- (1) ORFS Male (2) ORFS Male Bulkhead	 FF1284LN- (2) ORFS Male Bulkhead (1) & (3) ORFS Male	 FF1236- (1) ORFS Male (2) ORFS Fem. Swivel	 FF1227- (1) & (2) ORFS Male (3) ORFS Fem. Swivel	 FF1248- (1) & (3) ORFS Male (2) ORFS Fem. Swivel	 FF1231- (1) ORFS Male (2) O'RING BOSS Male
 FF1238- (1) ORFS Male (2) Adj. O'RING BOSS Male	 FF1240- (1) ORFS Male (2) Adj. O'RING BOSS Male	 FF1265- (1) & (2) ORFS Male (3) Adj. O'RING BOSS Male	 FF1266- (1) & (3) ORFS Male (2) Adj. O'RING BOSS Male	 FF1202- (1) ORFS Male (2) NPT Male	 FF1208- (1) ORFS Male (2) NPT Male	 FF1332- (1) ORFS Bulkhead Lock Nut
 FF3020- (2) ORFS Male (1) TUBE BORE	 FF3031- (use w/FF1311) (1) ORFS Fem. Face (2) TUBE BORE	 FF3019- (use w/FF1311) (1) ORFS Fem. Cap				

TECHNICAL INFORMATION

JIC (TUBE) & O'RING BOSS (ORB) ADAPTERS

Dash Size	-07	-08	-09	-12	-14	-17	-19	-21	-26	-30	-40
Thread Size	7/16	1/2	9/16	3/4	7/8	1 1/16	1 3/16	1 5/16	1 5/8	1 7/8	2 1/2
Threads Per Inch	20	20	18	16	14	12	12	12	12	12	12
Male O.D.	0.436	0.500	0.561	0.748	0.873	1.061	1.180	1.311	1.623	1.873	2.498
Fem. I.D.	0.394	0.457	0.512	0.693	0.807	0.985	1.090	1.233	1.544	1.796	2.422

NPT (PIPE) ADAPTERS

Dash Size	-02	-04	-06	-08	-12	-16	-20	-24	-32
Thread Size	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2
Threads Per Inch	27	18	18	14	14	11.5	11.5	11.5	11.5
Male O.D.	0.406	0.546	0.671	0.843	1.062	1.312	1.671	1.906	2.375
Fem. I.D.	0.359	0.468	0.593	0.750	0.953	1.203	1.531	1.781	2.250

O'RING FACE SEAL (ORFS)

Dash Size	-04	-06	-08	-10	-12	-16	-20	-24
Thread Size	9/16	11/16	13/16	1	1 3/16	1 7/16	1 11/16	2
Threads Per Inch	18	16	16	14	12	12	12	12
Male O.D.	0.560	0.690	0.820	1.000	1.190	1.440	1.690	2.000
Fem. I.D.	0.510	0.630	0.750	0.930	1.110	1.360	1.610	1.920

A LARGE RANGE OF BRITISH AND METRIC ADAPTERS ALSO IN STOCK