



Professional Grade Pressure Washing Equipment



Product Range Includes:

- Hoses in a Variety of Pressure Ratings, Lengths, and Non-Marring
- Wide Range of Tips: 0°, 15°, 25°, 40° and Turbo Nozzles
- Guns, Lances and Wands
- Brass Fittings
- Pressure Wash Couplers and Plugs
- Tanks and Tank Accessories
- Bulk Lengths
- Hose Reels
- Specialty Applications

Hose Features:

- Hoses Provide High Flexibility with Low Weight
- Excellent Resistant to Most Detergents
- Extremely High Abrasive Resistant Cover
- Hot and Cold Pressure Wash Applications

Product Benefits:

- Durable Industrial Quality
- Low Maintenance Equipment
- Adaptable
- Easy to Use



Available in Stores Now

www.pirtekusa.com

To Locate Your Nearest Service Center



Features

- Wrapped impression
- Maximum oil resistant tube and cover
- Superior flexibility
- Heavy duty PVC bend restrictors
- Bite - to - Wire couplings
- USA made swivels
- Temp: -40°F to +230°F (+275°F peak)
- Not for steam use

Pressure Washer Hose (R1) & (R2) - Wrapped Cover

PIRTEK Part Number	Hose Color	Hose I.D. (in.)	Hose O.D. (in.)	Rated W.P. (psi)	Min. Burst (psi)	Fittings 3/8 NPT	Hose Guard Color	Hose Guard Std.	Length (ft.)
PW4000-06-50 [†]	Black	3/8	0.64	4,000	12,000	F x SW	Black	6" x 6"	50
PW4000-06-100 [†]	Black	3/8	0.64	4,000	12,000	F x SW	Black	6" x 6"	100
PW4000B-06-50 ^{†*}	Blue	3/8	0.64	4,000	12,000	F x SW	Black	6" x 6"	50
PW4000B-06-100 ^{†*}	Blue	3/8	0.64	4,000	12,000	F x SW	Black	6" x 6"	100
PW6000-06-50 ^{†**}	Black	3/8	0.70	6,000	18,000	F x SW	Red	6" x 24"	50
PW6000-06-100 ^{†**}	Black	3/8	0.70	6,000	18,000	F x SW	Red	6" x 24"	100

*Non-Marking

**OSHA & UL-1776 Approved Bend Restrictors

[†] Not suitable for steam or hydraulic applications.

PIRTEK Branded Custom Lengths Available, Made to Your Requirements

- Wrapped impression
- Maximum oil resistant tube and cover
- Superior flexibility
- Heavy duty PVC bend restrictors available
- Bite - to - Wire couplings available
- Temp: -40°F to +230°F (+302°F peak)
- Not for steam use

PIRTEK Part Number	Hose Color	Hose ID		Hose OD		Rated Working Pressure PSI		Reinforcement
		in		in		Working	Min Burst	
PW4500-06 [†]	Black	3/8		0.64		4500	18,000	1 braid
PW4500B-06 ^{†*}	Blue	3/8		0.64		4500	18,000	1 braid
PW3600B-04 ^{†*}	Blue	6.4		0.50		3600	14,400	1 braid

*Non-Marking

[†] Not suitable for steam or hydraulic applications.

NOTE ALL HOSES: With temperatures greater than 230°F, the service life of the hose will be greatly reduced.